

**ELEVATORE IDRAULICO - ELEVATEUR HYDRAULIQUE
- HYDRAULIC FORKLIFT - HYDRAULIK-STAPLER -
ELEVADOR HIDRÁULICO**

**Elevatori idraulici con 2 sfili, per trattori.
Portata kg 1500**



**Elévateurs hydrauliques double télescopique, pour tracteurs.
Capacité de charge Kg 1500**



**Double telescopic hydraulic forklifts, for tractors.
Load capacity Kg 1500**




**2-stufiger Hydraulik-Stapler, für Traktoren.
Leistung Kg 1500**



**Elevadores hidráulicos telescópicos dobles, para tractores.
Capacidad de carga kg 1500**



MONDIAL		PORTATA CAPACITE DE CHARGE LOAD CAPACITY HEBEGEWICHT CAPACIDAD DE CARGA	ALTEZZA DI SOLLEVAMENTO HAUTEUR D' ELEVATION LIFTING HEIGHT HEBEHÖHE ALTURA DE ELEVACIÓN	BRANDEGGIO AVANTI INDIETRO INCLINAISON EN AVANT ET ARRIERE FORWARD/BACKWARD FORKS NACH-VORNE-KIPPEN MOVIMIENTO HACIA ADELANTE Y ATRÁS	TRASLATORE LATERALE TRANSLATEUR LATERAL SIDESHIFTER SEITENVERSTELLUNG DESPLAZADOR LATERAL
	kg	kg	mm		mm
3200	440	1500	3200	12° - 17°	100 + 100



A	3200 mm
B	2323 mm
C	300 mm

